

材料 E1001-64

### Crystal Setup File Parameters

Run Name: JAT3112800

Ref F: F @ 25.00 ĩC (Set)

Print: All Operator:

Run Start: 12-ĩA-2017 10:52 am

Row A: Measured FL

Row B: Measured FL

Run Finish: 12-ĩA-2017 11:27 am

S&A W2200 Rev: 6.60 Report: 2.17

Start: B002 Stop: B013  
 Setup: TEMPH900184  
 Reference F: 12,800,000 Hz CL: 20.00 pF Power: 100.00 uW into 25.00 Ohms Measure: FR/T

	TEMP ĩC	FL ppm	C0 pF	RR Ohms	Q k	C1 fF	DLD2 Ohms	FL MHZ	
B003<	89.98	-2.5	2.4<	52.3	427<	0.5566<	84.845<	12.799967	20170502071
									1
B003<	93.98	-2.2	2.4<	52.1	428<	0.5570<	127.760<	12.799971	20170502071
B003<	100.02	-0.3	2.4<	51.9	430<	0.5576<	27.342<	12.799996	20170502071
B005<	90.02	-3.4	2.5<	38.2	601<	0.5412<	22.640<	12.799956	20170502084
B005<	94.03	-3.3	2.5<	39.9	582<	0.5359<	13.669<	12.799958	20170502084
B005<	99.99	0.6	2.5<	44.1	538<	0.5240<	19.562<	12.800008	20170502084
B006<	90.01	-3.4	2.4<	38.9	589<	0.5434<	10.223<	12.799957	20170502075
B006<	93.96	-3.1	2.4<	38.7	591<	0.5440<	9.062<	12.799961	20170502075
B006<	100.02	-1.3	2.4<	38.2	596<	0.5454<	9.493<	12.799984	20170502075
B007<	90.01	-3.7	2.4<	49.5	491<	0.5116<	30.565<	12.799953	20170502070
B007<	93.99	-3.5	2.4<	55.4	454<	0.4941<	40.357<	12.799955	20170502070
B007<	99.99	-1.9	2.4<	70.0	383<	0.4643<	67.190<	12.799976	20170502070