

Standard (Wide)

Setup: BFM-170400696-SVO-1417  
 Path: D:\DATA\出货DATA\暂存\05261  
 Description: 大普通信(SVO-1417)  
 Reference Fr: 61,440,245 Hz Resolution: 0.200 ppm  
 Short<50 mA Open<0 mA Sense: 10 Ohms Print All

Low Pull  
 S&A 280A Revision: 8.70 Report 1.10

| STATUS | FR   | DUTY | I    | VH    | VL    | TR     | TF    | HIGH PULL | LINEARITY | LOW PULL |        |
|--------|------|------|------|-------|-------|--------|-------|-----------|-----------|----------|--------|
|        | ppm  | %    | mA   | V     | V     | nsecs  | nsecs | ppm       | %         | ppm      |        |
| 1      | Pass | -8.9 | 50.1 | 8.161 | 4.174 | -0.770 | 1.343 | 1.363     | 86.5      | 6.1      | -119.7 |
| 2      | Pass | -7.9 | 50.0 | 8.037 | 4.240 | -0.732 | 1.320 | 1.356     | 108.0     | 5.9      | -145.1 |
| 3      | Pass | -8.9 | 50.0 | 7.944 | 4.205 | -0.720 | 1.297 | 1.328     | 115.1     | 5.9      | -150.9 |
| 4      | Pass | -7.1 | 50.1 | 7.966 | 4.177 | -0.661 | 1.300 | 1.335     | 89.4      | 5.5      | -115.4 |
| 5      | Pass | 1.7  | 50.1 | 8.181 | 4.219 | -0.776 | 1.329 | 1.330     | 87.4      | 6.2      | -107.8 |
| 6      | Pass | -8.8 | 50.0 | 8.278 | 4.124 | -0.742 | 1.323 | 1.320     | 102.0     | 6.4      | -130.5 |
| 7      | Pass | -7.9 | 50.5 | 7.921 | 4.132 | -0.692 | 1.268 | 1.271     | 117.2     | 5.6      | -144.4 |
| 8      | Pass | -7.0 | 50.2 | 7.943 | 4.213 | -0.695 | 1.314 | 1.358     | 82.7      | 6.8      | -126.8 |
| 9      | Pass | -5.0 | 50.1 | 7.796 | 4.129 | -0.685 | 1.319 | 1.338     | 107.3     | 5.7      | -125.7 |
| 10     | Pass | -0.6 | 50.2 | 8.122 | 4.185 | -0.693 | 1.294 | 1.303     | 87.6      | 5.6      | -102.3 |



Siward Crystal Technology Co.,Ltd

FQC Report

PRINTING: 17/05/26 14:15:20

FROM: 洪麗如 PAGE: 1/1

FQC NO. : OVC-170500012 LOT NO : BFM-170400696  
 PART NO. : 1059506144000001 ORDER NO: S11-170301715-1  
 P/N Spec : V011 /3.3 /HCMOS30p/C/N/1417 CUST.NO : 206069-大普通信  
 30 /-40,85 / /2.97,0.33 End User:  
 SAMPLING : N-1-2 LOT SIZE : 9000  
 QC Date : 2017/5/26 TIME : 14:14:05

PASS : 9000 JUDGEMENT: ACCEPT INSPECTOR: 洪麗如

| NO. | INSP. | ITEM           | CR/MA/MI | AQL  | VL | AC | RE | SAMPLE | DEFECT | RESULT |
|-----|-------|----------------|----------|------|----|----|----|--------|--------|--------|
| 1   | 6F01  | ELECTRICAL     | MA       | 0.25 | 2  | 0  | 1  | 200    | 0      | AC     |
| 2   | 6F02  | APPEARANCE(MA) | MA       | 0.25 | 2  | 0  | 1  | 200    | 0      | AC     |
| 3   | 6F03  | APPEARANCE(MI) | MI       | 1.00 | 2  | 0  | 1  | 200    | 0      | AC     |

※SPEC. VER. :4 17/01/17

※BFM-170400696:8612

※BRW-170400992:388

※CUSTOMER P/N:Z53YX61441

※SIWARD P/N:VCX953300-SVO-1417

※CUSTOMER PO:201703285

※CUSTOMER REQUEST:

This product does not contain the substances  
 whose application is forbidden By RoHS.

(aqcr340)

APPROVE:



CHECK:



INSPECTOR:



QAD-029

(END)