

产品型号	稳定日准确度	准确度判定	牵引范围	牵引范围判定
X3225YF19443	1.7 19440003.7	OK	-12907.6 12714.16	OK
X3225YF19443	1.7 19439978.2	NG	-10894.2 13590.02	不合格
X3225YF19443	1.7 19439994.7	OK	-10665 13866.08	OK
X3225YF19443	1.7 19440005.9	OK	-10685.9 13396.6	OK
X3225YF19443	1.7 19440007.2	OK	-10625.2 13515.09	OK
X3225YF19443	1.7 19439996.5	OK	-10928.5 13736.63	OK
X3225YF19443	1.7 19439982.1	OK	-10892.7 13724.97	OK
X3225YF19443	1.7 19439987.3	OK	-10292.7 13014.4	OK
X3225YF19443	1.7 19439986.6	OK	-10852.2 13643.86	OK
X3225YF19443	1.7 19439982.6	OK	-10327.8 13156.04	OK
X3225YF19443	1.7 19439975.9	NG	-10791.7 13579.22	不合格
X3225YF19443	1.7 19439983.4	OK	-10998.3 13892.49	OK
X3225YF19443	1.7 19440005.9	OK	-10432.4 13123.29	OK
X3225YF19443	1.7 19439975.3	NG	-10591.4 13479.42	不合格
X3225YF19443	1.7 19440005.2	OK	-10924 13976.85	OK
X3225YF19443	1.7 19440011.9	OK	-10250 12934.5	OK
X3225YF19443	1.7 19439987.6	OK	-10583 13268.52	OK
X3225YF19443	1.7 19439988.7	OK	-10294.2 12949.07	OK
X3225YF19443	1.7 19439980.9	OK	-10739.7 13690.84	OK
X3225YF19443	1.7 19439980.5	NG	-10866.1 13753.77	不合格
X3225YF19443	1.7 19440009.7	OK	-10951.1 13832.65	OK
X3225YF19443	1.7 19439987.6	OK	-10160.7 12858.71	OK
X3225YF19443	1.7 19439984.1	OK	-10697.2 13450.1	OK
X3225YF19443	1.7 19439983.4	OK	-10594.3 13455.59	OK
X3225YF19443	1.7 19440003.2	OK	-10801.1 13815.33	OK
X3225YF19443	1.7 19439983.6	OK	-10893.3 13682.44	OK
X3225YF19443	1.7 19440005.8	OK	-10356 12876.37	OK
X3225YF19443	1.7 19439978.3	NG	-10972.7 13792.7	不合格
X3225YF19443	1.7 19439985.4	OK	-10865.9 13750.86	OK
X3225YF19443	1.7 19440009.9	OK	-11064.8 13753.77	OK