

Travelling Merchant: _____

DATASHEET

Standard: DPBA16733210

Plot			The Label
Drew	Audited	Approved	Stamp, please! Thanks!
Date: 2017.09.28			

Guangdong Dapu Telecom Technology Co.,Ltd

Bldg13-16,.N.Ind.Zone,SSL Industry Park, Dongguan City, Guangdong Province, China

TEL: 0086-0769-88010888 FAX: 0086-0769-81800098




1、 Electrical Parameters

MODEL: DPBA16733210							
No.	Parameters	SYM	Electrical Spec.				Notes
			Min.	Typ.	Max.	Units	
1	Nominal Frequency	FL	167.332			MHz	
2	Output Waveform	-	LVPECL				
3	Supply Voltage	Vcc	3.13	3.3	3.47	V	
4	Rise/Fall Time	-	-	-	1.0	nS	@25°C
5	Output Load	-	50Ω-2V			-	
6	Frequency Stability	-	-25	~	+25	× 10 ⁻⁶	Include Freq. Tolerance, Temp.,Supply voltage, Load.
7	Operating Temperature Range	-	-40	~	+85	°C	
8	Storage Temperature	-	-55	~	+125	°C	
9	Tri-state(Output Active)		2.31 or Floatin	-	-	V	Pin 2 Tri-state Enable High
10	Tri-state(Output in High-Impedance state)		-	-	0.99	V	
11	Current Consumption	-	-	-	75	mA	
12	Output Level Logic 1	Voh	2.275	-	-	V	
13	Output Level Logic 0	Vol	-	-	1.68	V	
14	Duty Cycle	-	45	50	55	%	
15	Start Time	-	-	-	3.0	mS	
16	Aging	-	-3	~	+3	× 10 ⁻⁶	Frequency drift in first year
17	jitter				0.7	ps	(12KHz to 20MHz)
18	Phase noise				-90	dBc/ Hz	100Hz
					-120	dBc/ Hz	1KHz
					-130	dBc/ Hz	10KHz
					-140	dBc/ Hz	100 KHz
19	Thermal Shock	-55°C, 125°C; soak time is 10 mins, with total 200 cycles					
20	Vibration	Test Condition: 10~2000Hz, 1.52mm, 20g, each axis for 4 hrs					
21	Mechanical Shock	1500g, half-sine, 0.5ms, each axis for 3 times.					




2. Mechanical Structure(mm)



Note1: Tolerance ±0.2mm

3. Recommended Ir Reflow Profile



IR-Reflow Test

Reference Standard : JEDEC-STD 020


Test Conditions: Pre-heating : 150°C to 200 °C, 60~120 sec

Heating : 217 °C , 60~150 sec

Peak Temperature : 260±5 °C, 25±5 sec



4. Package: Tape & Reel (mm)



DAPU Confidential