

SAMPLE TEST DATA

Frequency : 115.20000 MHz
 Load Cap. : 30.0 pF
 Drive Level : 2.0 uW

Holder : SEG12

Order No. : SH-18X009

Q/N No. : 241956
 Date : Nov. 21, '18
 Inspector : S. KOBAYASHI

Serial No.	Room Temperature (+25°C)		Temperature Drift (Reference to R.T.)		Co	Q					
	F(MHz)	$\Delta F/F(\text{ppm})$	ESR(Ω)	$\Delta F/F(\text{ppm})$			ESR(Ω)	pF			
Spec.	+50 ~+20	Ω max.	\pm ppm	Ω max.	\pm ppm	Ω max.					
			50.0	50.0	50.0	min.					
1	115.204193	36.40	27.8	-4.14	29.9	-7.43	29.1	1.43	100413		
2	115.204216	36.60	27.9	-7.35	29.5	-5.36	29.3	1.41	96939		
3	115.203974	34.50	25.5	-11.83	28.5	0.84	26.6	1.44	105432		
4	115.204251	36.90	26.2	-6.72	27.7	-4.50	26.3	1.41	106630		
5	115.204193	36.40	27.5	-8.89	29.5	-3.21	27.4	1.38	98573		
6	115.204355	37.80	28.5	-8.89	31.4	-1.48	29.0	1.36	97103		
7	115.203894	33.80	28.3	-12.21	30.2	1.36	28.4	1.41	93155		
8	115.204090	35.50	25.3	-7.09	27.2	-4.28	25.5	1.40	106407		
9	115.204355	37.80	26.8	-7.89	28.1	-3.38	27.3	1.37	102263		
10	115.204159	36.10	24.3	-11.35	25.9	0.33	25.0	1.38	110381		
MAX.	115.204355	37.80	28.5	-4.14	31.4	1.36	29.3	1.44	110381		
MIN.	115.203894	33.80	24.3	-12.21	25.9	-7.43	25.0	1.36	93155		
AVG.	115.204168	36.18	26.8	-8.64	28.8	-2.71	27.4	1.40	101730		
SIG.	0.000141	1.22	1.4	2.43	1.5	2.75	1.5	0.02	5141		

KYUSHU DENTSU CO., LTD.

Approved: *[Signature]*