

Travelling Merchant: _____

DATASHEET

Standard: GX-32254-32.00MHZ

Plot			The Label
Drew	Audited	Approved	Stamp, please! Thanks!
Date: _____			

Guangdong Dapu Telecom Technology Co.,Ltd

Bldg13,.N.Ind.Zone,SSL Industry Park, Dongguan City, Guangdong Province, China

TEL: 0086-0769-88010888 FAX: 0086-0769-81800098




1、Electrical Parameters


MODEL: GX-32254-32.00MHz							
No.	Parameters	SYM.	Electrical Spec.				Notes
			Min.	Typ.	Max.	Units	
1	Nominal Frequency	FL	32.00			MHz	
2	Oscillation Mode	-	Fundamental				
3	Load Capacitance	CL	12			pF	
4	Frequency Tolerance	-	-10		+10	ppm	at 25°C± 3°C
5	Frequency Stability	-	-10		+10	ppm	Over Operating Temp. Range (Reference 25°C)
6	Operating Temperature Range	-	-20	~	+70	°C	
7	Aging	-	-2		+2	ppm	1st Year
8	Drive Level	DL	-	50	-	uW	
9	Series Resonant Resistance	Rr	-	-	50	Ω	
10	Shunt Capacitance	C0	-	-	-	pF	
11	Insulation Resistance	-	500	-	-	MΩ	at DC 100V
12	Storage Temperature Range	-	-40	~	+85	°C	
13	Drop Test	100 cm height, 3 times on concrete floor.					JIS C6701
14	Mechanical Shock	Device are shocked to half sine wave (1000 G) three mutually perpendicular axes each 3 times. 0.5m sec. duration time					MIL-STD-202F
15	Vibration	Frequency range			10 ~ 2000 Hz		MIL-STD-883E
		Amplitude			1.52 mm/20G		
		Sweep time			20 minute		
		perpendicular axes each test time			4 hours		
		(Total test time 12 hours)					



2、Mechanical Structure(mm)



3、Reflow Soldering Curve (RoHS)





4、 Package: Tape & Reel (mm)

