

客户宝号: _____
Travelling Merchant

DATASHEET

品名规格: **RM-7600**
Standard _____

编号: **15-0828**
P/N _____

出图 Plot			承认印 The Label
制图 Drew	审核 Audited	核准 Approved	请于承认签章 谢谢! Stamp, please! Thanks!
日期: Date:			


广东大普通信技术有限公司

东莞市松山湖科技产业园区北部工业城 16 栋

Guangdong Dapu Telecom Technology Co.,Ltd

Bldg16,.N.Ind.Zone,SSL Industry Park, Dongguan City, Guangdong Province, China

TEL: 0086-0769-88010888 FAX: 0086-0769-81800098




RM-7600

Long Range & Low Power

434/470/868/915MHz

LoRa™ Module



INTRODUCTION

The RM-7600 is a secure, CE/FCC certified, low-power RF module, that provides long-range, low bit rate transmitting data to RF applications.

With Class A functionality implemented, the RM-7600 is LoRaWAN™ 1.0 compliant. By using sub-GHz ISM bands, the RM-7600 providing bi-directional data communication up to 15 km line-of-sight and over 2 km into harsh environment.


The secure transmission with security protocols such as 'Packet engine up to 256 bytes with CRC', the long battery by fitting with ultra low power consumption transceiver, the easier connectivity with superior transmit power and receive sensitivity.

FEATURES

- ◇ LoRa™ Modem
- ◇ 168 dB maximum link budget
- ◇ +20 dBm- 100 mW constant RF output vs. V supply
- ◇ +14 dBm high efficiency PA
- ◇ Programmable bit rate up to 300 kbps
- ◇ High sensitivity: down to -148 dBm
- ◇ Bullet-proof front end: IIP3 = -11 dBm
- ◇ Excellent blocking immunity
- ◇ Low RX current of 9.9 mA, 200 nA register retention
- ◇ Fully integrated synthesizer with a resolution of 61 Hz
- ◇ FSK, GFSK, MSK, GMSK, LoRa™ and OOK modulation
- ◇ Built-in bit synchronizer for clock recovery
- ◇ Preamble detection
- ◇ 127 dB Dynamic Range RSSI
- ◇ Automatic RF Sense and CAD with ultra-fast AFC
- ◇ Packet engine up to 256 bytes with CRC

APPLICATIONS

- Automated Meter Reading
- Home and Building Automation
- Wireless Alarm and Security Systems
- Industrial Monitoring and Control
- Long range Irrigation Systems
- Other M2M Systems





1. 工作参数 Running Parameters

型号 MODEL : RM-7600					
指标描述 Description	指标 Parameters			单位 Unit	测试条件 Test Condition
	最小值 Min.	典型值 Typ.	最大值 Max.		
供电电压 Supply voltage	2.4	3.3	3.7	V	
工作温度 Operational temperature range	-40	XX	85	°C	
电流特性 Power consumption	休眠模式 Sleep Idle	XX	2	XX	uA
	待机模式 Standby	XX	2	XX	mA
	接收 Receive Mode	XX	12	XX	mA
	发射 Transmit Mode	XX	110	XX	mA
晶振频率 Crystal oscillator frequency	XX	32	XX	MHz	
制式 Modulation	FSK/LoRa				
通信芯片 Transceiver	SX1276				
MCU	NA				

2. 性能指标 Performance Parameters

指标描述 Description	指标 Parameters	单位 Unit
工作频率 Frequency Range	137~1020	MHz
扩频 Spread Frequency	6~12	
带宽 Bandwidth	7.8~500	KHz
有效波特率 Effective Bitrate	0.018~37.5	kbps
灵敏度 Est. sensitivity	-110~-148	dBm
发射功率 RF output	10~19	dBm
数据包传输 Packet engine	256 bytes with CRC	



3. PIN 示意图及外观图 Pin Diagram & Package Marking


相连引脚号/ Connected pin No.			
RF 板 /Board	SX1276	引脚定义/Pin definition	说明/Description
1	16	SCK	SPI Clock input
2	17	MISO	SPI Data output
3	18	MOSI	SPI Data input
4	19	NSS	SPI Chip select input
5	20	RXTX	Rx/Tx switch :high in Tx
6	7	ESET	Reset trigger input
7	0/15/21/23/26	GND	GND
8	3/14/24	VDD	VDD_3.3V
9		ANT_HF	ANT_HF
10		ANT_LF	ANT_LF
11		CTS	ANT_HF 射频开关:高电平发射/ANT_HF Enable port: high in Tx
12		CPS	ANT_LF 射频开关:高电平发射/ANT_LF Enable port: high in Tx
13	13	DI05	Digital I/O
14	12	DI04	Digital I/O
15	11	DI03	Digital I/O
16	10	DI02	Digital I/O
17	9	DI01	Digital I/O
18	8	DI00	Digital I/O



引脚示意图/ Pin Diagram


Not marked tolerance : $\pm 0.2\text{mm}$

Number	Name	Pin Description
1	SCK	
2	MISO	
3	MOSI	
4	NSS	
5	RXTX	
6	ESET	
7	GND	
8	VDD	
9	ANT_HF	
10	ANT_LF	
11	CTX	
12	GPS	
13	DI05	
14	DI04	
15	DI03	
16	DI02	
17	DI01	
18	DI00	





4. 产品型号说明/ Product model description:



5. 抽样测试结果表/ Sample test results table

发射测试/TX Test					接收测试/RX Test						
工作频点 /Frequency	发射功率设置 /Setting	实测发射功率 /Transmit Power	实测发射电流 /Transmit Current	扩频实测/Spread Frequency MHz					接收灵敏度 /Sens.	扩频因子 /SF	接收工作电流 /cur.
				868	1302	1736	2170	2604			
434MHz	17 dBm	16.13 dBm	82 mA	-57.3	-58	-73	-73	-73	-139dBm	SF=12	12mA
	20 dBm	18.31 dBm	106 mA	-57	-57.4	-74	-73	-73			
470MHz				940	1410	1880	2350	2820	-139dBm	SF=12	12mA
	17 dBm	15.94 dBm	80 mA	-50	-62	-70	-73	-73			
	20 dBm	18 dBm	103 mA	-50	59	-74	-73	-73			
868MHz				1736	2604	3472	4340	5208	-137dBm	SF=12	11mA
	15 dBm	14.25 dBm	37 mA	-35	-45	-34.5	-65	-70			
915MHz				1830	2745	3660	4575	5490	-137dBm	SF=12	12mA
	15 dBm	14.17 dBm	38 mA	-33	-52	-38	-70	-70			
待机/standby current			2mA		频率误差/Frq error				+4KHz		