

Travelling Merchant: \_\_\_\_\_

# DATASHEET

Standard: OS754-A319-29.4912MHz

Plot			The Label
Drew	Audited	Approved	Stamp, please! Thanks!
Date: 2020.03.25			

## Guangdong Dapu Telecom Technology Co.,Ltd

Bldg13,.N.Ind.Zone,SSL Industry Park, Dongguan City, Guangdong Province, China

TEL: 0086-0769-88010888 FAX: 0086-0769-81800098




## 1、Electrical Parameters

MODEL: OS754-A319-29.4912MHz							
No.	Parameters	SYM.	Electrical Spec.				Notes
			Min.	Typ.	Max.	Units	
1	Nominal Frequency	FL	29.4912			MHz	
2	Frequency Stability	-	-25		+25	ppm	
3	Operating Temperature Range	Topr	-40	25	85	°C	
4	Storage Temperature Range	Tstg	-55	~	125	°C	
5	Supply Voltage	VDD	3.3±10%			V	
6	Input Current	Icc	-	-	15	mA	
7	Output Load: CMOS	CL	15			pF	
8	Output Voltage High	VoH	90% Vdd	-	-	V	
9	Output Voltage Low	Vol	-	-	10% Vdd	V	
10	Rise Time	Tr	-	-	6	ns	10%-90% VDD Level
11	Fall Time	Tf	-	-	6	ns	90%-10% VDD Level
12	Symmetry (Duty ratio)	TH/T	45	~	55	%	
13	Start-up Time	Tosc	-	-	10	ms	
14	Aging	-	±3			ppm/yr.	1st. Year at 25°C
15	Drop Test	75 cm height,3 times on concrete floor.					JIS C6701
16	Mechanical Shock	Device are shocked to half sine wave ( 1000 G ) three mutually perpendicular axes each 3 times. 0.5m sec. duration time					MIL-STD-202F
17	Vibration	Frequency range 10 ~ 2000 Hz Amplitude 1.52 mm/20G Sweep time 20 minute perpendicular axes each test time 4 hours (Total test time 12 hours)				MIL-STD-883E	




## 2、 Mechanical Structure (mm)



Note: #1. DLD2 / Drive Level Dependency 2 Maximum resistance minus minimum resistance.

## 3、 Reflow Soldering Curve (RoHS)





#### 4、 Package: Tape & Reel (mm)

