




## DP3096C

### ENG PART:DP-15.5CM-2300T2400-CCW

2300MHz to 2400MHz Single-Junction Surface Mount Circulator

REV.	DESCRIPTION	REVISOR	DATE	APPROVED
A	SAME AS REV.3	ZC.Wu	2024/6/27	Nick




#### Applications:

- Wireless Infrastructure
- Power Amplifier

#### Features:

- Operating frequency range: 2300MHz to 2400MHz
- Operating temperature range: -40°C to +125°C
- Storage temperature range: -50°C to +125°C
- Small surface-mount package delivered on T&R
- BeOfree&RoHS compliant



Block Diagram

**Electrical Specifications:**


ITEM	SPECIFICATION	
Frequency	2300~2400	MHz
Direction	CCW	
Impedance	Typ: 50	$\Omega$
Insertion Loss (Max.)	0.20@-40~+115 $^{\circ}$ C	dB
	0.25@+115~+125 $^{\circ}$ C	
Isolation (Min.)	23	dB
Return Loss (Min.)	23@0~125 $^{\circ}$ C	dB
	20@-40~0 $^{\circ}$ C	
3rd IMD (Max.)	-69@2x50W , 5MHz spacing	dBc
5th IMD (Max.)	-79@2x50W , 5MHz spacing	dBc
Harmonics	60@ 2 x TX (100W CW )	dBc
	60@ 3 x TX (100W CW )	
Out of band attenuation	20@2xTX	dB
	10@3xTX	
	5@nxTX	
Group delay	0.4~2.0	ns
Reciprocity	-0.05~+0.05 @Delta(S21 / S32) within any 10 $^{\circ}$ C temperature range	dB
	-1~+1 @Delta(S21 / S32) within any 10 $^{\circ}$ C temperature range	Deg
Deviation from nominal delay over temperature range	$\pm 0.05$ (Measured with fixed frequency)	ns
Power FWD/REV/PEAK	100/100/1000	W
Max voltage rating	1080	V
Input Impedance (real)	50 $\pm$ 2.5	$\Omega$
Input Impedance (Imaginary)	$\pm 2.5j$	$\Omega$
Output Impedance	50	$\Omega$
Resonance out of	2100~2600	MHz
Termination/Attenuator	/-	W/dB

## Notes:

1. Exposure to maximum rating conditions for extended periods may reduce device reliability. There is no damage to device with only one parameter set at the limit and all other parameters set at or below their nominal value. Exceeding any of the limits listed here may result in permanent damage to the device.
2. Performance is guaranteed under the conditions listed in this table and over the operating temperature range.



Mechanical Specifications:



Unit: Millimeters

Notes:

1. The housing and pins are silver-plated.
2. Tolerance  $\pm 0.2$  mm unless otherwise specified.
3. Co-planarity Specification: 0.1 mm maximum.
4. Part Number, Lot Code, and Port Designation are printed on the top side of device
5. The **XXXXXXX** on the label represents the part number
6. The **SSSSSS** on the label represents the serial number
7. The black dot on the label represents the input port



Packaging Style:

ITEM	W	A0	B0	K0	D	E	F	F2	P	P0	P2	T
DIM	44	Φ15.5	Φ18.3	7.3	Φ1.5	1.75	20.2	40.5	28	4	2	0.5
TOLE	±0.3	±0.2	±0.2	±0.2	+0.1	±0.1	±0.15	±0.1	±0.1	±0.1	±0.1	±0.05

